

NORMA GOST 2679-93								NORMA GOST 2679-93							
Rozměry pily								Zuby - kl. t 1							
Ø pily - D	Ø otvoru - d	síla pily	Tolerance	Podbrus		výpočet podbrusu	Počet zubů	úhel čela	úhel rozteče	hloubka zubu	patní rádius - r				
				podbrus 1/2 úhel	mm							celkem podbrus			
63	16	0,3	0,38-0,45	5'	0,02	0,04	0,34-0,41	64	0°	60°	1,56	0,5			
		0,4	0,48-0,55	10'	0,05	0,10	0,38-0,45								
		0,5	0,58-0,65				0,48-0,55								
		0,6	0,68-0,75	15'	0,07	0,14	0,54-0,61	48	5°	60°	1,74	0,8			
		0,8	0,88-0,95				30'						0,14	0,28	0,60-0,67
		1,0	1,08-1,15	0,80-1,01											
		1,2	1,36-1,46	1°	0,27	0,54	1,08-1,18	40	10°	60°	2,32	1,0			
		1,6	1,76-1,86				1,48-1,58								
		2,0	2,16-2,26				1,88-1,98								
		2,5	2,66-2,76	1°	0,27	0,54	2,12-2,22	32	10°	60°	2,18	1,0			
		3,0	3,16-3,26				2,62-2,72								
		4,0	4,18-4,30				3,64-3,76								
		5,0	5,18-5,30	1°	0,27	0,54	4,64-4,76	24	10°	60°	4,36	1,0			
		6,0	6,18-6,30				5,64-5,76								
80	22	0,5	0,58-0,65	5'	0,06	0,12	0,46-0,53	64	5°	60°	1,59	0,8			
		0,6	0,68-0,75	15'	0,08	0,16	0,52-0,59								
		0,8	0,88-0,95				0,72-0,79								
		1,0	1,08-1,15	30'	0,17	0,34	0,74-0,81	48	10°	60°	2,25	1,0			
		1,2	1,36-1,46				1°						0,34	0,68	1,02-1,12
		1,6	1,76-1,86												1,42-1,52
		2,0	2,16-2,26	1°	0,34	0,68	1,82-1,92	40	10°	60°	2,75	1,3			
		2,5	2,66-2,76				1,98-2,08								
		3,0	3,16-3,26				2,48-2,58								
		4,0	4,18-4,30	1°	0,34	0,68	3,5-3,62	32	10°	60°	3,16	1,3			
		5,0	5,18-5,30				4,5-4,62								
		6,0	6,18-6,30	1°	0,34	0,68	5,5-5,62								



